# **Material Safety Data Sheet**



Zep Inc. 1310 Seaboard Industrial Blvd. Atlanta, GA 30318 1-877-I-BUY-ZEP (428-9937) www.zep.com Section 1. Chemical Product and Company Identification

Product name AEROSOLVE II

**Product use** Aerosol Solvent Degreaser

Product code 0181

Date of issue 03/19/09 Supersedes 10/08/04

**Emergency Telephone Numbers** 

**For MSDS Information:** 

Compliance Services 1-877-I-BUY-ZEP (428-9937)

For Medical Emergency

(877) 541-2016 Toll Free - All Calls Recorded

For Transportation Emergency

CHEMTREC: (800) 424-9300 - All Calls Recorded In the District of Columbia (202) 483-7616

Prepared By

Compliance Services 1420 Seaboard Industrial Blvd.

Atlanta, GA 30318

Section 2. Hazards Identification

Printing date: 03/19/09

**Emergency overview** 

\*Hazard Determination System (HDS): Health, Flammability, Reactivity

0

WARNING!

CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

VAPOR HARMFUL. CONTENTS UNDER PRESSURE.

NOTE: MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.

Acute Effects Routes of Entry Dermal contact. Inhalation.

**Eyes** Causes eye irritation. Inflammation of the eye is characterized by redness, watering and itching.

**Skin** Causes skin irritation. Skin inflammation is characterized by itching, scaling, reddening or,

occasionally, blistering.

**Inhalation** Avoid inhalation of vapor, spray or mist. Over-exposure by inhalation may cause respiratory

irritation. Can cause central nervous system (CNS) depression. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of

consciousness.

**Ingestion** Aspiration hazard if swallowed. Can enter lungs and cause damage.

<u>Chronic effects</u> Repeated or prolonged exposure to the substance can produce damage to central nervous system,

peripheral nervous system, kidneys, liver and heart. May cause hearing impairment or change.

Prolonged skin contact may cause dermatitis with drying and cracking of skin.

Carcinogenicity Trichloroethylene: Classified + (Proven) by OSHA. Classified Group 2A (Probable for Human)

by IARC. Group 2 (Reasonably Anticipated To Be Human Carcinogen) by NTP.

Additional Information: See Toxicological Information (Section 11)

Section 3. Composition/Information on Ingredients

TRICHLOROETHYLENE; acetylene trichloride; 1-chloro-2,2-dichloroethylene 79-01-6 >90 CARBON DIOXIDE 124-38-9 1 - 5

Section 4. First Aid Measures

**Eye Contact** Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and

remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

**Skin Contact** Wash affected area with soap or mild detergent and water. Remove contaminated clothing and shoes. Continue

to rinse for at least 10 minutes. Wash clothing before reuse. Get medical attention if irritation develops.

**Inhalation** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

Get medical attention immediately.

**Ingestion** Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting unless directed to do

so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.

Never give anything by mouth to an unconscious person. Get medical attention immediately.

Page: 1/3

Product code 0181 Material Safety Data Sheet Product Name AEROSOLVE II

### Section 5. Fire Fighting Measures

Flash Point Not applicable.

Flammable Limits Not applicable.

Flammability Non-flammable. (CSMA)

Fire hazard CONTENTS UNDER PRESSURE. Container explosion may occur under fire conditions or

when heated. Vapors may accumulate in low or confined areas or travel a considerable distance

to a source of ignition and flash back.

Fire-Fighting Use dry chemical or CO<sub>2</sub>. Cool closed containers exposed to fire with water. Wear special

**Procedures** protective clothing and positive pressure, self-contained breathing apparatus.

#### Section 6. Accidental Release Measures

**Spill Clean up** Large spills are unlikely due to packaging.

# Section 7. Handling and Storage

**Handling** Put on appropriate personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Do not

breathe vapor or mist. Use only with adequate ventilation. Watch for accumulation in low confined areas.

Storage Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section

10) and food and drink. Do not store above the following temperature: 49°C (120.2°F). Do not puncture or incinerate

container. Keep out of the reach of children.

### Section 8. Exposure Controls/Personal Protection

## Product name Exposure limits

TRICHLOROETHYLENE; acetylene trichloride; 1-chloro-2,2-

dichloroethylene

ACGIH TLV (United States).
TWA: 10 ppm 8 hour(s).
STEL: 25 ppm 15 minute(s).
OSHA PEL (United States).
TWA: 50 ppm 8 hour(s).
STEL: 200 ppm 15 minute(s).
ACGIH TLV (United States).

CARBON DIOXIDE

ACGIH TLV (United States).

TWA: 5000 ppm 8 hour(s).

STEL: 30000 ppm 15 minute(s).

#### **Personal Protective Equipment (PPE)**

**Eyes** Recommended: Safety glasses.

**Body** Recommended: Chemical-resistant gloves. Viton

**Respiratory** Use with adequate ventilation. Provide exhaust ventilation or other engineering

controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this

is necessary.

## Section 9. Physical and Chemical Properties

Physical State<br/>pHLiquid. (Aerosol.)<br/>Not applicable.Color Clear. Colorless.<br/>Odor Mild. Solvent.Boiling Point87.22°C (189°F)Vapor Pressure Not available.

Specific Gravity 1.46 Vapor Density Not available.

Solubility Insoluble in the following materials: cold water and

hot water.

Evaporation Rate <1 (Carbon tetrachloride = 1)

VOC (Consumer) 96.9% 11.78 (lb/gal) 14

VOC (Consumer) 96.9% 11.78 (lb/gal) 1412 (g/l).

# Section 10. Stability and Reactivity

**Stability and Reactivity** The product is stable.

**Incompatibility** Reactive or incompatible with the following materials: oxidizing materials, metals and alkalis.

**Hazardous Polymerization** Will not occur.

Hazardous Decomposition Products Carbon dioxide, carbon monoxide, Hydrogen chloride (HCl), Chlorine and Phosgene gas.

National Fire Protection Association (U.S.A.)



Page: 2/3

Product code 0181 Material Safety Data Sheet Product Name AEROSOLVE II

# Section 11. Toxicological Information

**Acute Toxicity** 

Product/ingredient name Result Species Dose Exposure

 Trichloroethylene
 LD50 Dermal
 Rabbit
 10000 mg/kg

 LD50 Oral
 Rat
 4920 mg/kg

 LD50 Oral
 Mouse
 2402 mg/kg

# Section 12. Ecological Information

#### **Aquatic Ecotoxicity**

**Waste Information** 

Not available.

## Section 13. Disposal Considerations

#### Coolion for Diopocar Conciderati

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

Waste Stream Code: D040, U228

Classification: - [Hazardous waste.]

Origin: - [RCRA waste.]

# Section 14. Transport Information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label
DOT Classification	None.	Consumer commodity ORM-D			
IMDG Class	Not determined.				

NOTE: DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

PG\* : Packing group

# Section 15. Regulatory Information

### **U.S. Federal Regulations**

SARA 313 toxic chemical notification and release reporting:

# Product name

Trichloroethylene

Clean Water Act (CWA) 307: Trichloroethylene (RQ 100 lbs.) Clean Water Act (CWA) 311: Trichloroethylene (RQ 100 lbs.)

Clean Air Act (CAA) 112 regulated toxic substances: Trichloroethylene

All Components of this product are listed or exempt from listing on TSCA Inventory.

#### **State Regulations**

**California Prop 65 WARNING:** This product contains a chemical or chemicals known to the state

of California to cause cancer, birth defects or other reproductive harm.:

Trichloroethylene

## Section 16. Other Information

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

\*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.