



## MATERIAL SAFETY DATA SHEET

**Product name:** GC22  
**Description:** Aerosol propellant for use with Hilti GX 120 fastening tool  
**Supplier:** Hilti, Inc. P.O. Box 21148, Tulsa, OK 74121  
**Emergency # (Chem-Trec.):** 1 800 424 9300 (USA, PR, Virgin Islands, Canada); 703 527 3887 (Other countries)

## INGREDIENTS AND EXPOSURE LIMITS

Ingredients:	CAS Number:	TLV:	PEL:	STEL:
Isobutane	75-28-5	1000 ppm	NE	NE
Propylene	115-07-1	860 mg/m <sup>3</sup>	NE	NE
Propane*	74-98-6	1000 ppm	1800 mg/m <sup>3</sup>	NE

\* Propane remains in the can and is not released.

**Abbreviations:** PEL = OSHA Permissible Exposure Limit. TLV = ACGIH Threshold Limit Value. STEL = Short Term Exposure Limit. NE = None Established. ppm = Parts per million.

## PHYSICAL DATA

<b>Appearance:</b>	Colorless aerosol.	<b>Odor:</b>	Sweet petroleum odor.
<b>Vapor Density: (air = 1)</b>	Not determined.	<b>Vapor Pressure:</b>	4793 mm Hg @ 68 F.
<b>Boiling Point:</b>	Not determined.	<b>VOC Content:</b>	Not determined.
<b>Evaporation Rate:</b>	Not determined.	<b>Solubility in Water:</b>	Negligible.
<b>Density:</b>	1.28 g/cm <sup>3</sup> @ 68 F.	<b>pH:</b>	Not applicable.

## FIRE AND EXPLOSION HAZARD DATA

<b>Flash Point:</b>	Not applicable.	<b>Flammable Limits:</b>	LEL = 1.3% UEL = 11.1%
<b>Extinguishing Media:</b>	Carbon Dioxide, Dry Chemical, Foam, Water		
<b>Special Fire Fighting Procedures:</b>	Extremely flammable aerosols. Cool with water spray to prevent ignition.		
<b>Unusual Fire and Explosion Hazards:</b>	Extremely flammable. Contents under pressure. Containers exposed to fire can burst or be propelled through the air.		

## REACTIVITY DATA

<b>Stability:</b>	Stable.	<b>Hazardous Polymerization:</b>	Will not occur.
<b>Incompatibility:</b>	Strong oxidizing agents.		
<b>Decomposition Products:</b>	Thermal decomposition can yield CO and NO <sub>x</sub> .		
<b>Conditions to Avoid:</b>	Potential ignition sources such as extremely hot surfaces, flames, sparks, static discharges, etc.		

## HEALTH HAZARD DATA

<b>Known Hazards:</b>	Irritation. Direct contact with contents can cause irritation or frostbite.		
<b>Signs and Symptoms of Exposure:</b>	<b>Contact:</b> No effects expected from normal use. Direct contact with liquefied gas (e.g. from a leaking can) can cause irritation and possibly burns (i.e. frostbite). <b>Inhalation:</b> No ill effects expected from normal use. Contains asphyxiant gases. Direct inhalation of gases can cause narcotic effects. <b>Ingestion:</b> Not a likely route of exposure.		
<b>Routes of Exposure:</b>	Dermal. Inhalation.		
<b>Carcinogenicity:</b>	No ingredients are classified as a carcinogen by IARC, NTP or OSHA.		
<b>Medical Conditions Aggravated by Exposure:</b>	Eye, skin, and respiratory conditions.		

## EMERGENCY AND FIRST AID PROCEDURES

<b>Eyes:</b>	For contact with liquefied gas, flush immediately with plenty of water and seek medical attention.
<b>Skin:</b>	If contact with liquefied (cold) gases occurs, rinse affected area thoroughly with warm running water. Do not use hot water. Do not rub the skin. Contact a Physician if symptoms occur.
<b>Inhalation:</b>	Move victim to fresh air. Call a physician if symptoms persist.
<b>Ingestion:</b>	Not a likely route of exposure.
<b>Other:</b>	Referral to a physician is recommended if there is any question about the seriousness of the injury / exposure.

## CONTROL MEASURES AND PERSONAL PROTECTIVE EQUIPMENT

<b>Ventilation:</b>	General (natural or mechanically induced fresh air movements).
<b>Eye Protection:</b>	Safety glasses with side shields.
<b>Skin Protection:</b>	Leather or heavy cloth gloves are recommended.
<b>Respiratory Protection:</b>	None normally required. Where ventilation is inadequate to control vapors, use NIOSH-approved respirator with organic vapor cartridges.

## PRECAUTIONS FOR SAFE HANDLING AND USE

<b>Handling and Storing Precautions:</b>	Store in a cool dry area preferably between 41 and 77° F. Do not store in direct sunlight. Do not store with DX cartridges (Boosters). Extremely flammable gas under pressure. Keep away from excessive heat, sparks, flames and any other potential ignition sources. Do not allow liquefied gases to come in contact with the skin. Use with adequate ventilation. For industrial use only. Keep out of reach of children. Follow label / use instructions.
<b>Spill Procedures:</b>	Immediately remove any ignition sources. Wear appropriate personal protective equipment. Provide adequate ventilation to disperse gases.

## REGULATORY INFORMATION

<b>Hazard Communication:</b>	This MSDS has been prepared in accordance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200.
<b>HMIS Codes:</b>	Health 1, Flammability 4, Reactivity 0, PPE B
<b>DOT –Ground Shipping Name:</b>	Limited Quantity - LQ
<b>IATA (air) Shipping Name:</b>	Devices, small, hydrocarbon gas powered <i>with release device</i> , Class 2.1, UN3150
<b>TSCA Inventory Status:</b>	Chemical components listed on TSCA inventory.
<b>SARA Title III, Section 313:</b>	This product contains up to 20% Propylene (CAS #115-07-1) which is subject to reporting under Section 313 of SARA Title III (40 CFR Part 372).
<b>EPA Waste Code(s):</b>	D001
<b>Waste Disposal Methods:</b>	Consult with regulatory agencies or your corporate personnel for disposal methods that comply with local, state, and federal safety, health and environmental regulations.

## CONTACTS

<b>Customer Service:</b>	1 800 879 8000
<b>Technical Service:</b>	1 800 879 8000
<b>Health / Safety:</b>	1 800 879 6000 Jerry Metcalf (x1003704)
<b>Emergency # (Chem-Trec):</b>	1 800 424 9300 (USA, PR, Virgin Islands, Canada); 703 527 3887 (Other countries)

The information and recommendations contained herein are based upon data believed to be correct; however, no guarantee or warranty of any kind expressed or implied is made with respect to the information provided.