

**MATERIAL SAFETY DATA SHEET**  
COMPLIES WITH OSHA'S HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

**SECTION I · PRODUCT IDENTIFICATION**

**Product Name:** Cutting and Tapping Fluid  
**Product Number:** 875  
**Product Type:** AEROSOL  
**Formula:** Proprietary  
**Supplier's Name:** Terand Industries, Inc.  
**Supplier's Address:** P.O. Box 667770, Pompano Beach, FL 33066  
**DOT Ship Description:** CONSUMER COMMODITY, ORM-D

**Date Prepared:** 11/01/07

**Information Phone:** (954) 974-5440  
**Emergency Phone:** (800) 535-5053

**HMIS Rating (Based on Aerosol Conc.):**  
0-Minimal 1-Slight 2-Moderate  
3-Serious 4-Extreme

HEALTH:	1
FLAMMABILITY:	3
PHYSICAL HAZARD:	0
Personal Protection:	B

**SECTION II · INGREDIENTS**

<u>CHEMICAL NAME</u>	<u>CAS #</u>	<u>%WT</u>	<u>313/Chem</u>	<u>Skin</u>	<u>Carcinogen</u>	<u>PEL</u>	<u>TLV-TWA</u>
Ethyl Alcohol	64-17-5	40-50	NO	NO	NO	1000 ppm	1000 ppm
Polyalkylene Glycol Monobutyl Ether	9038-95-3	10-20	NO	NO	NO	N/E	N/E
Amine containing alcohol	Trade Secret *	1-10	NO	NO	NO	N/E	N/E
Liquefied Petroleum Gas	68476-86-8	20-40	NO	NO	NO	1000 ppm	1000 ppm

\* Massachusetts Trade Secret Code No. = 99-206-098

**SECTION III · PHYSICAL DATA**

**Aerosol Concentrate:**  
**Boiling Point:** 170 °F  
**pH:** N/A  
**Appearance/Odor:** Clear liquid with alcohol odor  
**Specific Gravity (H<sub>2</sub>O=1)@70 °F:** 0.862  
**Solubility In Water:** Complete  
**Vapor Density(Air=1):** >1

**Total Contents:**  
**Total VOC %:** 78.36%  
**Vapor Pressure (can; psig @72 °F):** 50

**SECTION IV · FIRE AND EXPLOSION DATA**

**Flash Point (Conc.):** 41 °F (T.C.C.)  
**Extinguishing Media:** Water Fog, Foam, CO<sub>2</sub>, Dry Media  
**Special Fire Fighting Procedures:** Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing.  
**Unusual Fire and Explosion Hazards:** Exposure to temperature above 120 °F may cause bursting.  
**Flammability (as per CSMA Flame Projection Test):** Extremely Flammable Spray

**SECTION V · REACTIVITY DATA**

**Stability:** Material Stable.  
**Incompatibility:** Avoid contact with halogens, strong acids, strong bases, and strong oxidizing agents.  
**Hazardous Decomposition Products:** Material decomposed by fire may produce oxides of carbon, nitrogen, and phosphorous.  
**Hazardous Polymerization:** Will not Occur.

**SECTION VI · STORAGE AND HANDLING**

**KEEP OUT OF REACH OF CHILDREN.**  
**For Industrial and Institutional use only.**  
**Store in a cool, dry area away from heat or open flame.**  
**Do not store at temperatures above 120 °F.**  
**NFPA Code 30B Rating:** Level 3 Aerosol.

**SECTION VII · HEALTH AND FIRST AID**

**PRIMARY ROUTES OF ENTRY & EFFECTS OF OVER EXPOSURE:**

**Eyes:** May cause irritation and corneal inflammation.  
**Skin:** Frequent or prolonged contact may cause irritation and/or dermatitis. May aggravate existing skin conditions.  
**Inhalation:** Inhalation of vapors or mist can cause irritation of nasal and respiratory passages, dizziness, and headache. Repeated or prolonged inhalation of mist can produce delayed lung damage, possibly progressing to death.  
**Ingestion:** Can cause gastrointestinal irritation, nausea, vomiting, diarrhea, and depression of the central nervous system. Prolonged ingestion may cause liver damage, "fetal alcohol syndrome" in pregnant females, and neuronal degeneration. Aspiration of material into the lungs can cause severe pulmonary injury.

**FIRST AID PROCEDURES:**

**Eyes:** Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.  
**Skin:** Wash with soap and water. If irritation persists seek medical attention.  
**Inhalation:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.  
**Ingestion:** Do not induce vomiting. Seek medical attention immediately.

**SECTION VIII · SPECIAL PROTECTION DATA**

**Respiratory Protection:** None needed for proper use in accordance with label directions.  
**Ventilation:** Provide local exhaust.  
**Protective Gloves:** Wear solvent resistant gloves to prevent skin contact.  
**Eye Protection:** Always wear safety glasses or chemical proof goggles when working with chemicals.

**SECTION IX · SPILL OR LEAK PROTECTION**

**STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK:** Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.

**WASTE DISPOSAL METHOD:** Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.

N/A= NOT APPLICABLE · N/E=NOT ESTABLISHED · N/D=NOT DETERMINED · <=LESS THAN · >=MORE THAN

**NOTICE:** The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive nor fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.