



MATERIAL SAFETY DATA SHEET

GENERAL INFORMATION

PRODUCT NAME OR NUMBER (as it appears on label)	CATALOG NUMBER			
ClearGlide™ Wire Pulling Lubricant	All "31" Series			
MANUFACTURER'S NAME	EMERGENCY TELEPHONE NO.			
IDEAL INDUSTRIES, INC.	(815) 895-5181			
ADDRESS (Number, Street, City, State, Zip Code)				
Becker Place, Sycamore, IL 60178				
HAZARDOUS MATERIÁL DESCRIPTION, PROPER SHIPPING NAME, HAZARD CLASS, HAZARD CLASS, HAZARD ID NO. (49 CFR 172.101)				
None				
CHEMICAL DESCRIPTION	FORMULA			
Polymer-based Mixture	Proprietary			

SECTION I - INGREDIENTS

CAS REGISTRY NO.	%W	CHEMICAL NAME(S)*	Listed as a carcinogen in NTP, I ARC or OSHA 1910(z) (specify)
7732-18-5	<98	Water	No
6440-58-0	<1	DMDM Hydantoin No	
9038-95-3	<5	Oxirane, Methyl-, Polymer With Oxirane, No	
		Monobutyl Ether	
9003-11-6	<1	Amino-Methyl-Propanol	No
25322-68-3	<1	Polyethylene Glycol	No
9003-01-4	<1	Carbomer Thickener	No
68037-64-9	<1	Silicone Glycol Blend	No

SECTION II - PHYSICAL DATA

BOILING POINT	SPECIFIC GRAVITY (H ₂ O=1)	PERCENT VOLATILE BY VOLUME (%)		
212°F °C	1.09	<98		
SOLUBILITY IN WATER	pH =	PERCENT SOLID BY		
Infinite	7.0 - 8.0	WEIGHT (%) ~5		
APPEARANCE AND ODOR		IS MATERIAL: LIQUID SOLID (GEL)		
Clear, colorless	GAS PASTE POWDER			

SECTION III - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT	None	method used C.O.C	FLAMMABLE LIMITS	LEL	UEL
				None	None
EXTINGUISHING M	IEDIA				
		Use extinguishing media	suitable for surrounding mat	terials.	
SPECIAL FIRE FIG	HTING PROCED	DURES			
			None		
UNUSUAL FIRE AND EXPLOSION HAZARDS					
None					

^{*} None of the chemical raw materials contained in this formulation are considered hazardous under the Federal Hazards Communication Standard 29 C. F. R 1910.1200

SECTION IV - HEALTH HAZARD INFORMATION

EFFECTS OF OVER	EVDOCUDE Cond	itiona to	Avoid			
EFFECTS OF OVER	REXPOSURE - Colla	ונוטווא נט		xpected. U	Jpon pro	olonged contact, may cause temporary eye
discomfort.					F - F -	
THRESHOLD LIMIT	VALUE					_
PRIMARY ROUTES	OF ENTRY Inhalation	on 🔲	Skin Contact Other (specify)	<u> </u>		
EMERGENCY FIRST	T AID PROCEDURE	S				
SKIN CONTACT: EYE CONTACT:		V	lash with soap and water for 1	5 minutes.		
INGESTION:		F	lush with water for 15 minutes.	Inhalatio	n - Move	e to fresh air.
INOLOTION.	A	dminis	ster water or milk. Consult oh SECTION V - RE			
	UNSTABLE		CONDITIONS TO AVOID		I DAIR	1
STABILITY	STABLE	Χ	Avoid prolo	onged stor	age at te	emperatures exceeding 190 F.
INCOMPATIBILITY (-	^				
	,		Avoid strong oxid	lizers and	nitrites	
HAZARDOUS DECC	OMPOSTION PRODU	JCTS:	Oxides of carbon, n	itrogen an	d silicon	ne
	MAY OCCUR		CONDITIONS TO AVOID			
HAZARDOUS POLYMERIZATION					N	lone
OETWIENZ/(TON	WILL NOT OCCU	R X				
			SECTION VI - SPILL AN	ID LEAK	PROCI	EDURES
STEPS TO BE TAKE	EN IF MATERIAL IS	RELEA			-11	
as they can h	e dangerously	slinr		el or vacui	ım soille	d material. Clean up spills immediately
WASTE DISPOSAL	METHOD	<u> </u>	,o.y.			
		С	omply with Federal, state or lo	cal regulat	tions for	solid landfill.
CERCLA (Superfund	I) REPORTABLE QU	ANTIT	Y (in lbs)			
RCRA HAZARDOUS	S WASTE NO. (40CE	R 261	N/	Α		
	•		N/	A		
VOLATILE ORGANI	C COMPOUND (VO	C) (as p	packaged, minus water) 17.4 gr	me / Itr		
³ Theoretical	Ib/gal N/A		17.4 UI	³ Analytical _	lb/ga	al N/A
		SE	CTION VII - PERSONAL P	ROTECT	ION IN	FORMATION
RESPIRATORY PRO	OTECTION (specify t					
10	OCAL EVHALIST (See	ocify Do	None norma None None		d. ECIAL	None
VENTILATION						
			commended in closed areas.	OT	HER	None
PROTECTIVE GLOV	/ES (specify type) one normally red	quired	EYE PROTECTION (specify type) J.		glasses	or splash goggles.
OTHER PROTECTIV	/E EQUIPMENT					
			Fve fountain in work a SECTION VIII - SPEC			
PRECAUTIONS TO	BE TAKEN IN HAND	I ING A		JIAL PRE	CAUI	IONS
THEOMOTIONS TO	DE ITALEN INTENTAL	ZEII (O)	Store at temperatures betwee	n 40 - 180	F. Avoi	id freezina.
OTUED DDEGALITY	2112					
OTHER PRECAUTION	JNS		Keen away from child	ren infants	s and ne	ets
			SECTION IX - ADDITI			
N/A = Not App	licable, N.E. =	None	e Established			
		TI	HIS MATERIAL SAFETY D	ATA SHE	ET PRI	EPARED BY:
. —				OLONIATI		
NAME Da	arryl Docter			SIGNATI	JRE	
	arryl Docter anager Quality	Assu		SIGNAT		Slarryl blocke

