PRODUCT SAFETY DATA SHEET

Sheet 1 of 4 Date: March 2013 Revision: 4

FLUID FILM® NON-AEROSOL (NAS)

1. Chemical Product and Company Identification

Name of Manufacturer/Supplier: Eureka Chemical Company

Address & Phone No. 24 Hour Telephone

234 Lawrence Avenue Chemtrec (800) 424-9300

South San Francisco, CA 94080

USA Tel: (650) 761-3536 Fax: (650) 589-1943

Product Name: FLUID FILM® NON-AEROSOL (NAS) **Product Type:** Liquid, Lubricant, Corrosion Inhibitor

HAZARD RATING

 N
 4 - EXTREME
 HEALTH
 C

 F
 3 - HIGH
 FIRE
 1

 P
 2 - MODERATE
 REACTIVITY
 C

 A
 1 - SLIGHT
 SPECIAL

0 - INSIGNIFICANT

2. Hazards Information

Eye Contact: May cause mild irritation.

Skin Contact: Prolonged contact could cause irritation.

Inhalation: Prolonged exposure to mist without benefit of protective gear may

irritate respiratory tract.

Ingestion: No information available.

3. Composition/Information on Ingredients

Contains no solvents or known carcinogens. **Hazardous components:**CAS No.

Petroleum Oil Mist

64742-54-7

(Only when sprayed)

4. First Aid Measures

Eye Contact: Flush with plenty of clean water for at least 15 minutes. If irritation persists,

obtain medical attention.

Skin Contact: Wipe excess material from the skin with a cloth, followed by washing with soap

and water. A waterless skin cleanser is beneficial in removing the material from

the skin.

Inhalation: If respiratory symptoms develop, move victim away from source of exposure

and into fresh air. If symptoms persist, seek medical attention.

Ingestion: If symptoms develop, seek medical attention.

Product Name FLUID FILM® NON- AEROSOL (NAS)

Product Type: Liquid, Lubricant, Corrosion Inhibitor

5. Fire Fighting Measures

Flash Point: 207°C (404°F) (COC)

Extinguishing

Media: CO₂, Dry Chemical, Foam

Special Fire

Fighting Procedures: None

Unusual Fire and

Explosion Hazards: None

6. Accidental Release Measures

Do not allow product to enter drains or water courses. Transfer bulk of material into another container. Absorb remaining residue with proper absorbents such as earth or vermiculite. Sweep up and dispose of as solid waste in accordance with applicable regulations.

7. Handling and Storage

Storage Temperature: 0 - 49°C

Storage Precautions:

No special requirements. Keep in closed containers.

Handling:

Avoid contact with skin and eyes. Observe good

standards of industrial hygiene.

8. Exposure Controls/Personal Protection

Engineering Measures: Provide forced air ventilation in tanks and confined spaces.

Respiratory Protection:Use approved respirator with organic vapor cartridges when spray applying in tanks and confined spaces.

Eyes: Use chemical eye goggles when spray applying.

Hand:Non-natural, non-butyl rubber gloves are recommended.
Skin:
Use protective clothing. Remove contaminated clothing and

wash the affected area with soap and water.

Exposure Limits: Not determined.

9. Physical and Chemical Properties

Appearance: Straw colored liquid. Odor: Mild piney odor (less propellant). Water Solubility: Not soluble. pH Neat: 7.8 Specific Gravity (25°C): 0.880 Freezing Point: Not determined. Vapor Pressure: Not determined. Boiling Point: Not determined. Flash Point: 207°C (COC). VOC: <1% (CARB 310).

10. Stability and Reactivity

Stability: Stable under normal conditions. Hazardous polymerization will not occur.

Hazardous Decomposition Products: Combustion can produce a variety of compounds including oxides of sulfur, oxides of carbon, water vapor and unidentified organic and inorganic compounds, some of which may be toxic.

Sheet 2 of 4

Sheet 3 of 4

Product Name: FLUID FILM® NON-AEROSOL (NAS) **Product Type:** Liquid, Lubricant, Corrosion Inhibitor

Conditions to Avoid: Exposed flames, high temperature sources and strong oxidizers.

11. Toxicological Information

LD50 (Animal/Oral): Greater than 14 Grams/Kilogram

Health Effects:

Eyes: Minimally irritating.

Skin: Prolonged contact could cause skin irritation.

Inhalation: Excessive exposure due to lack of protective gear or proper ventilation could result in pulmo-

nary abnormalities.

Ingestion: Ingestion of this product is not regarded as a significant health hazard likely to arise in normal

use.

12. Ecological Information

No data available.

13. Disposal Consideration

Product should be disposed of via authorized waste disposal contractors in accordance with all local and national regulations.

14. Transport Information

Non-hazardous.

15. Regulatory Information

Safety Phrases: Children can fall into bucket and drown. Keep children away from buckets containing even a small amount of water.

Keep out of reach of children.

SARA TITLE III:

Hazard Category for Section 311/312: Acute Health, Fire Hazard, Sudden Release of Pressure **Section 313 Toxic Chemicals:** This product contains no chemicals subject to SARA Title III Section 313 reporting requirements.

Section 302 Extremely Hazardous Substances (TPQ): None

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65): This product does not contain chemicals regulated under California Proposition 65.

VOC Regulations: This product complies with the consumer product VOC limits of CARB, the US EPA and states adopting the OTC VOC rules.

EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA Inventory.

16. Other Information

Do not mix with other chemicals.

Product Name: FLUID FILM® NON-AEROSOL (NAS)

Sheet 4 of 4

Product Type: Liquid, Lubricant, Corrosion Inhibitor

This data sheet does not constitute an assessment of the workplace risks as required under the provisions of the Health & Safety at Work act and the Control of Substances Hazardous to Health (COSHH).

Legal Disclaimer: The information supplied above is based upon the present state of our knowledge of the product at the time of publication. It is given in good faith and no warranty is implied with respect to the specification or quality of the product. The user must satisfy himself that the product is entirely suitable for his purpose.