

MSDS 0055060

[5506](#): Heet Antifreeze Gas Line 12 Oz [24]
 MSDS Last updated: 02/11/2010

[Print](#)
[Go Back](#)
[All MSDS](#)

IMPERIAL SUPPLIES LLC MSDS SHEET FOR 5506
 28201 - HEET Gas Line Antifreeze

SECTION 1 - CHEMICAL PRODUCT AND MANUFACTURER IDENTIFICATION

Product Name: 28201 - HEET Gas Line Antifreeze
 Part Number: 28201
 Product CAS: (None)
 Product Code: 28201
 Synonyms: 28201 - HEET Gas Line Antifreeze

MANUFACTURER IDENTIFICATION

Name: Gold Eagle Company
 Address: 4400 S. Kildare Blvd
 City: Chicago State: IL Zip: 60632-4372

For information call: 773-376-4400
 Emergency Number: N/A
 Emergency Agency: INFOTRAC
 Agency Number: 1-800-535-5053
 MSDS Effective Date: 1/1/1980
 MSDS Supersedes Date: 4/8/2008
 Miscellaneous:
 Product CAS: Mixture
 Brief Description: Gas line dryer and antifreeze for automobiles.

SECTION 2 - COMPOSITION, INFORMATION ON INGREDIENTS

Chemical Name	CAS	MIN	MAX
Methanol	67-56-1	99	99
Proprietary Additive	(none)	1	1

Miscellaneous:
 CHEMICAL NAME LIMIT VALUES
 Methanol PEL 200 ppm
 Proprietary Additive (CAS#: Mixture) N/A

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

NFPA: Health: 1 Fire: 3 Reactivity: Specific Hazard: None
 0
 HMIS: Health: 1 Flammability: 3 Reactivity: PPE: B
 0

Miscellaneous:

This product does not contain any components above de minimus concentrations that are considered carcinogenic by OSHA, IARC or NTP.

POTENTIAL HEALTH EFFECTS

Target Organs/Primary Route(s) of Entry:

Eye: Mild Irritant
 Skin: Prolonged or repeated skin contact may cause dermatitis, scaling and possible systemic effects.

Ingestion: POISON-Oral human lowest lethal dose = 6.4 g/kg

Inhalation Poisonous, narcotic chemical affecting central nervous system
 : resulting in: dizziness, nausea, visual impairment, narcosis and muscular impairment.

Miscellaneous:

SECTION 4 - FIRST AID MEASURES

Eye: If the product contacts the eyes, immediately wash the eyes with large quantities of room temperature water for at least 15 minutes, occasionally lifting the lower and upper lids. Get medical attention immediately. A follow up visit to an ophthalmologist should be made. Contact lenses should not be worn when working with this chemical.

Skin: If the product contacts the skin, promptly wash the contaminated skin with soap and water for at least 15 minutes. If this product penetrates the clothing, promptly remove the clothing and wash the skin with soap and water. Systemic effects may be delayed 18-72 hours, therefore keep individual under observation.

Ingestion: If this product is ingested and the person is conscious, induce vomiting, then give 2 teaspoons of baking soda in a glass of water. DO NOT INDUCE AN UNCONSCIOUS PERSON TO VOMIT. Get medical attention immediately.

Inhalation: Move the exposed person to fresh air at once and call emergency medical care. If breathing has stopped, give artificial respiration. IF breathing is difficult, give humidified oxygen.

Notes to Physician: No data available.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point: 52 F. (11 C.) TOC

Auto-Ignition Temperature: N/A

Flammable Limits

Lower Limit:	Explosive Limit (LEL):	6.0
Upper Limit:	Explosive Limit (UEL):	36.5

Extinguishin g Media: Use halon replacement or carbon dioxide extinguishers or alcohol foam for small fires. Water spray or fog can cool fire but may not be effective in extinguishing fires. Large fires should be extinguished with alcohol foam. Use water spray to cool containers exposed to fire. Containers may explode in heat or fire.

Unusual Fire and Explosion Hazards: Dangerous fire and explosion hazard when exposed to heat or flames. Methanol is extremely flammable and forms explosive mixtures with air. Methanol vapors may travel considerable distance to a source of ignition and flash back.

Special Fire Fighting Procedures: Wear NIOSH approved SCBA respirator in the positive pressure mode and chemical protective clothing.

General Information: Flammable Limits: 6.0 to 36.5

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Small Spill: Remove sources of heat or ignition, provide adequate ventilation, contain leak using absorbent, inert, non-combustible material.

Large Spill: Contain spill, transfer to secure containers. In the event of an uncontrolled material release, the user should determine if release is reportable under applicable laws and regulations.

SECTION 7 - HANDLING AND STORAGE

Handling: See other sections of MSDS.

Storage: See other sections of MSDS.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

GENERAL HYGIENE CONSIDERATIONS: Use normal hygiene practices.

OTHER: Methanol waste and material contaminated with methanol would be

PRECAUTIONS: regulated as a hazardous waste material under the hazardous waste number U154.

ENGINEERING CONTROLS:

Local Exhaust: Provide local ventilation to maintain exposure levels below recommended exposure limits.

Mechanical (General): In confined spaces, mechanical ventilation may be required.

Special Ventilation: N/A

Other Ventilation: N/A

PERSONAL PROTECTIVE EQUIPMENT

Eyes/Face: Use splash proof chemical, safety goggles or appropriate full-face respirator. Contact lenses should not be worn when working with this chemical.

Skin: Use natural rubber or neoprene gloves as required.

Respirators: Do not use air purifying respirator. Use NIOSH approved respirator approved supplied or self contained respirator. Respirators must be selected based on the airborne levels found in the workplace and must not exceed the working limits of the respirator.

Other Protective Clothing/Equipment: If there is a possibility of exposure of an individual's body to methanol, wear body covering work clothes to avoid prolonged or repeated exposure.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Odor: Yellow liquid, solvent odor

pH: N/A

Vapor Pressure: (MM HG): 97.0

Vapor Density (Air=1): 1.1

Evaporation Rate: N/A

Viscosity: N/A

Boiling Point: 148 F. (65 C.) N/A

Freezing/Melting Point: N/A

Decomposition Temperature: N/A

Solubility in Water: Soluble

Specific Gravity: 0.795

Molecular Formula: N/A

Molecular Weight: N/A

VOC Coating (minus water): 0 Lbs/Gallon

Coating Density: 0 Lbs/Gallon

Solvent Density: 0 Lbs/Gallon

Percent Solvent (volume): 0

Percent Solids (volume): 0

Percent Water (volume): 0

Percent Volatile by Weight: 0

Miscellaneous:

% Volatile/Volume 100.0

Specific Gravity (H2O=1): N/A

Percent Solvent (volume): 0

Percent Solids (volume): 0

Percent Water (volume): 0

Product is flammable, keep away from sources of ignition, combustibles, oxidizing material and acid. Store in an area equipped with automatic sprinklers or fire extinguishing system. Empty containers contain product residues; assume empty containers to have the same hazards as full containers.

SECTION 10 - STABILITY AND REACTIVITY

Chemical Stability:

Stable: Yes

Conditions to Avoid:

Store in a well ventilated place away from sources of ignition, combustibles, oxidizing materials and acid.

Incompatibilities with Other Materials:

Strong oxidizing agents, aluminum, zinc, or metals that displace hydrogen, rubber and rubber based coatings, chromic anhydride, lead perchlorate and perchloric acids.

Hazardous Decomposition Products:

Excessive heating and/or incomplete combustion will produce carbon monoxide.

Hazardous Polymerization:

Hazardous Polymerization May occur: No

SECTION 11 - TOXICOLOGICAL INFORMATION

No data available

SECTION 12 - ECOLOGICAL INFORMATION

No data available

SECTION 13 - DISPOSAL CONSIDERATIONS

Dispose of product in accordance with local, state and federal regulations. Before attempting clean up, refer to other sections of MSDS for hazard warning information.

SECTION 14 - TRANSPORT INFORMATION**Transportation Information:****Shipping Information (CFR 49 and IMDG):**

Proper Shipping Name: Gasoline Additive, N.O.I.

DOT Hazard Class: Consumer Commodity, ORM-D

DOT UN Number: None required

IMDG Shipping Name: Dangerous Goods in Limited Quantities of Class 3.2
(Methanol)

PGII**Label Information:**

No data available.

SECTION 15 - REGULATORY INFORMATION**SARA Title III:**

Section 302: None

Section 304: None

Section 311: Hazard categories - Fire Hazard=Yes; Acute=Yes and Chronic=Yes

Section 313: Methanol, CAS# 67-56-1, 99.0%

CERCLA:

Section 311 (b) (4): Requires discharges of crude oil and petroleum products in any kind or form to waters must immediately be reported to the National Response Center at (800) 424-8802.

SECTION 16 - ADDITIONAL INFORMATION

Disclaimer: Information presented herein is believed to be factual, as it has been derived from the works and opinions of persons believed to be qualified experts. However, nothing contained in this information is to be taken as warranty or representation for which the Gold Eagle Co. bears legal responsibility. The user should review any recommendations in the specific context of the intended use to determine whether they are appropriate.

Prepared by: Mike Profetto

The information contained in this MSDS was obtained from current and reliable sources, however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of Imperial Supplies LLC, Imperial will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this 'dfmt' shall be created or inferred by any statement in this 'dfmt'. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this 'dfmt'. The user is responsible for full compliance.

